



STICK WITH US



## TECHNICAL DATASHEET

### Spraybond X10 Universal Canister

**Zettex Europe B.V.**

Patrijsweg 1, 4791 RV Klundert

The Netherlands

+31 (0)888-93 88 39

[info@zettex.com](mailto:info@zettex.com)

[www.zettex.com](http://www.zettex.com)

---

#### Product description

Zettex Spraybond X10 is a fast-drying universal spray adhesive for use on most construction and industry materials.

#### Material

SBR Rubber.

#### Advantages

- Fast drying.
- Extremely powerful.
- High solids content.
- For universal use.
- Ready to use.
- DCM free.

#### Application areas

For bonding all kinds of carpet, foam, underlayment, isolation material, fabrics, MDF and all kinds of felt.

#### Utilization

Make the materials to be glued dry and free from dust and grease. Then gently spray the contact adhesive on both surfaces to be glued. A distance between substrate and spray gun of 30 cm is ideal. Apply the adhesive strips without overlapping. After 2-4 minutes glue both substrates together and press or roll firmly. In case of overlapping spraying at least double the open time. In the case of very porous substrates, check that there is sufficient contact between the two layers of adhesive. If necessary, apply an additional coat.

#### Packaging

- Canister 22 L

#### Color

Transparent.

#### Safety recommendations

Always read the safety information before use.

#### Shelf life

24 months in unopened packaging. Store at temperatures between 5°C and 25°C.

Properties	Specifications
Processing temperature	+5 to +40 °C
Temperature resistance	-40 to + 55°C
Consumption	70-80 gram/m2
Open time	2-3 min
Maximum yield	120 m2
Solids	32 %
Color	Transparent
Spray pattern	WEB